



**PRO PRIME
Latex Drywall Primer**

1090 Line

SECTION NO. 3 ADS-414

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Vinyl Acrylic Latex	Flat	350- 400 Sq Ft Per Gallon	Brush, Roller or Spray	Clean Water	Warm Soapy Water	1 Hour	2 Hours	7 Days
PRODUCT NAME: 1090 PRO PRIME LATEX DRYWALL PRIMER		An economy quality, fast drying vinyl primer and sealer for interior drywall. It is easy to apply, low in odor, and may be topcoated in four hours. It provides a good base for succeeding coats of latex or alkyd finishes. This product complies with LEED Green Building Rating System GS-11 for interior flat paints.						
WHERE TO USE:		Drywall Masonry	On interior wall surfaces prior to topcoating. Will provide an even seal and hold-out for subsequent finish coats.					
SURFACE PREPARATION:		Surface must be clean, dry and free of dirt, grease and grime. Remove all loose and flaking paint. Fill all holes, cracks and surface defects. Sand to smooth finish. Remove rust and prime all unpainted metal with O'Leary 560 Alkyd Primer or O'Leary 2090 Sungard Primer. Dull glossy surfaces by sanding. Prime new wood with O'Leary 50 Block It or 5790 Acrylic Primer. Prime new plaster and masonry with O'Leary Block It. Fill cinder block and rough masonry with 946-11 or 529-11 Block Filler. For best coverage primers and block fillers should be tinted to approximate finish color.						
APPLICATION:		Stir product thoroughly with a circular, lifting motion before you begin to paint. May be applied by brush, roller or spray, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will effect actual yield. For best results, use a quality synthetic filament brush. For roller application, use a 3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces and a 3/4" nap cover for rough surfaces. For spray application, may be thinned with clean water, up to 10% reduction if necessary. Satisfactory results are most likely obtained by using quality application tools. Apply when surface temperature is above 50° F.						
NOTE: Formulated without mercury or lead.								

RESIN TYPE:	Vinyl Acetate / Acrylic
SOLIDS:	Weight – 41.7% Volume – 27.9%
WEIGHT PER GALLON:	10.47 lbs.
VISCOSITY:	95– 100 (Krebs Units)
SPECULAR GLOSS:	1 – 2% @ 85 degrees
RECOMMENDED FILM THICKNESS:	Wet – 4.0 to 4.5 mils Dry – 1.0 to 1.2 mils
VOC – VOS STATEMENT:	This product contains less than 0.30 lbs or 35 GPL per gallon.
CAUTIONS:	CAUTION! Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

