



## Safety Data Sheet

Revision Date: February 6, 2017

Revision Number: #1

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** Duramax Polyurethane Semi-Gloss White  
**Product Code** 1213-00  
**Product Class** Solvent Thinned Paint  
**Color** All

**Manufacturer**  
 O'Leary Paint Company  
 415 Baker Street  
 Lansing MI 48910  
[www.olearypaint.com](http://www.olearypaint.com)

**Emergency Telephone Number(s)**  
 CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 191.0.1200)

Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1

#### Label elements

**Danger****Hazard statements**

May cause an allergic skin reaction

Suspected of causing cancer

May be fatal if swallowed and enters airways



**Appearance** liquid

**Odor** little or no odor

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Do not breathe dust/fume/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

If exposed or concerned get medical attention

**Skin**

If on skin wash with plenty of soap and water

If skin irritation or rash occurs get medical attention

Wash contaminated clothing before reuse

**Ingestion**

If swallowed immediately call a POISON CENTER or physician

Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not Applicable

**Other information**

No information available

**Other Hazards**

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight % (max)
Stoddard solvent	8052-41-3	30
Titanium dioxide	13463-67-7	25
Limestone	1317-65-3	15
Ethyl benzene	100-41-4	0.5
Methyl ethyl ketoxime	96-29-7	0.5
Cobalt bis(2-ethylhexanoate)	136-52-7	0.5

#### 4. FIRST AID MEASURES

<b>General Advice</b>	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
<b>Protection Of First-Aiders</b>	Use personal protective equipment
<b>Most Important Symptoms/Effects</b>	No information available.
<b>Notes To Physician</b>	Treat symptomatically

#### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective Equipment And Precautions For Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/N IOSH (approved or equivalent) and full protective gear.
<b>Specific Hazards Arising From The Chemical</b>	Combustible material. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors.
<b>Sensitivity To Mechanical Impact</b>	No
<b>Sensitivity To Static Discharge</b>	Yes

**Flash Point Data**

Flash Point (°F)	102
Flash Point (°C)	39
Flash Point Method	PMCC

**Flammability Limits In Air**

Lower Explosion Limit	Not available
Upper Explosion Limit	Not available

**NFPA**      **Health: 1**      **Flammability: 2**      **Instability: 0**      **Special: -**

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Use personal protective equipment. Remove all sources of ignition.
<b>Other Information</b>	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
<b>Methods For Clean-Up</b>	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.  <b>DANGER</b> - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.
<b>Incompatible Materials</b>	No information available

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Limits**

Chemical Name	ACGIH	OSHA
Stoddard solvent	100 ppm - TWA	2900 mg/m <sup>3</sup> - TWA 500 ppm - TWA
Limestone	2 mg/m <sup>3</sup> - TWA	15 mg/m <sup>3</sup> - TWA total 5 mg/m <sup>3</sup> - TWA
Titanium dioxide	10 mg/m <sup>3</sup> - TWA	15 mg/m <sup>3</sup> - TWA total
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 435 mg/m <sup>3</sup> - TWA
Methyl ethyl ketoxime	N/E	N/E
Cobalt bis(2-ethylhexanoate)	N/E	N/E

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Safety glasses with side-shields.

**Skin Protection**

Long sleeved clothing. Protective gloves.

**Respiratory Protection**

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	liquid
<b>Odor</b>	little or no odor
<b>Odor Threshold</b>	No information available
<b>Density (lbs/gal)</b>	10.55 – 10.75
<b>Specific Gravity</b>	1.27 – 1.29
<b>pH</b>	No information available
<b>Viscosity (cps)</b>	No information available
<b>Solubility</b>	No information available
<b>Water Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Wt. % Solids</b>	65 - 75
<b>Vol. % Solids</b>	45 - 55
<b>Wt. % Volatiles</b>	25 - 35
<b>Vol. % Volatiles</b>	45 - 55
<b>VOC Regulatory Limit (g/L)</b>	< 380
<b>Boiling Point (°F)</b>	315
<b>Boiling Point (°C)</b>	157
<b>Freezing Point (°F)</b>	32
<b>Freezing Point (°C)</b>	0
<b>Flash Point (°F)</b>	102
<b>Flash Point (°C)</b>	39
<b>Flash Point Method</b>	PMCC
<b>Flammability (solid, gas)</b>	Not available
<b>Upper Explosion Limit</b>	Not available
<b>Lower Explosion Limit</b>	Not available
<b>Autoignition Temperature (°F)</b>	No information available
<b>Autoignition Temperature (°C)</b>	No information available
	<b>Decomposition Temperature (°F)</b> No information available
	<b>Decomposition Temperature (°C)</b> No information available
<b>Partition Coefficient (n-octanol/water)</b>	No information available.

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Not Applicable
<b>Chemical Stability</b>	Stable under normal conditions. Hazardous polymerisation does not occur.
<b>Conditions To Avoid</b>	Keep away from open flames, hot surfaces, static electricity and sources of ignition.
<b>Incompatible Materials</b>	Incompatible with strong acids and bases and strong oxidizing agents.
<b>Hazardous Decomposition Products</b>	Thermal decomposition can lead to release of irritating gases and vapors.
<b>Possibility Of Hazardous Reactions</b>	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

<b>Inhalation</b>	No information available
<b>Eye contact</b>	No information available

---

**Skin contact** No information available  
**Ingestion** No information available

**Acute Toxicity**  
**Product** No information available

**Information on toxicological effects**

**Symptoms** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization:** Not available  
**Mutagenic Effects** Not available  
**Reproductive Effects** No information available

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 163529 mg/kg  
**ATEmix (dermal)** 65412 mg/kg

**Acute Toxicity**  
**Component**

Stoddard solvent

LD50 Oral: > 5000 mg/kg (Rat)  
LD50 Dermal: > 3160 mg/kg (Rabbit)  
LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)  
LD50 Dermal: > 5000 mg/kg (Rabbit)  
LC50 Inhalation (Vapor): 55000 mg/m<sup>3</sup> (Rat, 2 hr.)

Methyl ethyl ketoxime

LD50 Oral: 930 mg/kg (Rat)  
LD50 Dermal: 200 mg/kg (Rabbit)  
LC50 Inhalation (Vapor): > 4.8 mg/L (Rat)

Titanium dioxide

LD50 Oral: >10000 mg/kg (Rat)  
LD50 Dermal: >10000 mg/m<sup>3</sup> (Rabbit)  
LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4hr.)

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	IARC	NTP	OSHA Carcinogen
Ethyl benzene	2B - Possible Human Carcinogen		Listed
Cobalt bis(2-ethylhexanoate)	2B - Possible Human Carcinogen		
Titanium dioxide	2B - Possible Human Carcinogen		Listed

- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."
- Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

**Legend**

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity Effects****Product****Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence / Degradability**

No information available

**Bioaccumulation / Accumulation**

No information available

**Mobility in Environmental Media**

No information available

**Ozone**

No information available

**Component**



**Acute Toxicity to Fish**Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

**Acute Toxicity to Aquatic Plants**Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

**13. DISPOSAL CONSIDERATIONS****Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**Empty Container Warning**

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

**14. TRANSPORT INFORMATION****DOT**

<b>Proper Shipping Name</b>	Paint
<b>Hazard Class</b>	3
<b>UN-No</b>	UN1263
<b>Packing Group</b>	III

In the US this material may be reclassified as a Combustible Liquid and is not regulated in containers of less than 119 gallons (450 liters) via surface transportation (refer to 49CFR1 73.120(b)(2) for further information).

**ICAO / IATA**

Contact the preparer for further information.

**IMDG / IMO**

Contact the preparer for further information.

**15. REGULATORY INFORMATION**

**International Inventories**

**United States TSCA** Yes - All components are listed or exempt.  
**Canada DSL** Yes - All components are listed or exempt.

**Federal Regulations**

**SARA 311/312 hazardous categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name CAS-No	Weight % (max)
Ethyl benzene 100-41-4	0.5

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

Chemical Name	CAS-No	Weight % (max)
Ethyl benzene	100-41-4	0.5
Cobalt bis(2-ethylhexanoate)	136-52-7	0.5

**State Regulations**

**California Proposition 65**

*This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.*

**State Right-to-Know**

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Stoddard solvent	X	X	X
Ethyl benzene	X	X	X
Cobalt bis(2-ethylhexanoate)		X	X
Titanium dioxide	X	X	X

**Legend**

X - Listed

**16. OTHER INFORMATION**

**HMIS**Health: 1\*

**Flammability:** 2

**Reactivity:** 0

**PPE:** -

**HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

*Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.*

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**END OF SAFETY DATA SHEET**