



**H2O Clear  
Satin  
9612-99**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic Urethane	Satin	400-450 Sq Ft Per Gallon	Brush, Roller, or Spray	Clean Water	Warm Soapy Water	1 Hour	2 - 4 Hours	7 - 14 Days
<b>PRODUCT NAME:</b> H2O Urethane Acrylic Clear		H2O Acrylic Urethane Clear is an incredibly tough and durable waterborne clear finish that is easy to apply and has very low odor.						
<b>WHERE TO USE:</b>		Recommended for interior doors, trim, cabinets, furniture and residential floors. Ideal for use on properly prepared new wood surfaces as well as a topcoat over previously finished wood surfaces. H2O Clear may be used as a clear finish over painted surfaces and faux finishes to add stain and abrasion resistance. H2O clear has a slight amber cast so a test area is recommended over light colors.						
<b>Surface Preparation:</b>		Surfaces must be clean, dry and dull. Remove any wax, silicone or oil soap residue. H2O Clear can be used as both sealer and finish. In most applications at least two coats are required, on floors at least three coats are recommended.						
<b>Limitations:</b>		DO NOT APPLY H2O CLEAR OVER SANDING SEALERS OR FINISHES THAT CONTAIN STERATES. OIL BASED STAINS MUST BE THOROUGHLY DRY BEFORE APPLICATION OF H2O CLEAR. NOT FOR USE ON FLOORS THAT ARE WET CONTINUOUSLY.						
<b>Application:</b>		Stir thoroughly before using. Do not shake or mix with a high speed drill, doing so may result in bubbles in the finish. May be applied by brush roll or spray. Use a quality nylon/polyester brush and a 1/4" to 3/16" roller. May be thinned with up to 10% clean water when sprayed. Flow on generously working from the uncoated area into the coated area while maintaining a wet edge.						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin Type:</b>	Acrylic Urethane
<b>Volume Solids:</b>	27.4%
<b>Weight Per Gallon:</b>	8.61 lbs
<b>Viscosity:</b>	60 – 65 KU (Krebs Units)
<b>Specular Gloss:</b>	25 – 30% @ 60°
<b>Recommended Film Thickness:</b>	Wet – 4.0 mils Dry – 1.1 mils
<b>VOC – VOS Statement:</b>	This product contains a maximum of 94 grams of VOC per liter of coating
<b>Cautions:</b>	<p style="text-align: center;"><b>CAUTION!</b>  <b>Do not take internally. Close container after each use.</b></p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN.</b></p> <p style="text-align: center;"><b>PROTECT FROM FREEZING</b></p> <p style="text-align: center;"><b>Refer to the Safety Data Sheet for additional health &amp; safety information.</b></p>
<b>Warnings:</b>	<p><b>WARNING!</b> If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS A BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start find out how to protect yourself and your family by contacting the National Lead Information Hotline 1-800-424-LEAD or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>.</p>