



**Ceramic Pro
Vintage
Acrylic Matte
1851 Series**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic/ Vinyl Acrylic	Matte	Up to 400 - 450 Sq Ft Per Gallon	Brush, Roller, or Spray	Clean Water	Warm Soapy Water	1 Hour	4 Hours	7 - 10 Days
PRODUCT NAME: Ceramic Pro Vintage Matte Acrylic Enamel		Ceramic Pro Vintage Matte is a premium quality self-priming low sheen interior Matte finish that dries to a beautiful smooth finish. Vintage is spatter resistant has very good hide, superior washability and excellent touch-up.						
WHERE TO USE:		Recommended for interior walls and ceilings where a washable finish is required. Ideal for use on properly prepared drywall, plaster, masonry, wood and metal surfaces.						
Surface Preparation:		<p>New Work: The surface to be coated must be clean and free of oil, grease, rust and other contaminants that could interfere with adhesion.</p> <p>Priming – Drywall & Concrete – Self Priming or use Pro Prime 4190 Drywall Primer Wood – Block-It 50 Int/Ext Stain Blocking Primer or Alkyd Undercoat 37-11 Plaster – Block-It 50 Int/Ext Stain Blocking Primer</p> <p>Repaint: The surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust stains or loose flaking paint. Remove loose or flaking paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with this product or the appropriate primer.</p> <p>When using Vintage as primer/finish at least two coats are required.</p>						
Application:		<p>Stir thoroughly with a circular, lifting motion to assure even pigment dispersion.</p> <p>Roller – Use a 3/8" roller cover. Brush – Use a nylon / polyester brush. Spray – May be sprayed using airless equipment.</p> <p>For best results, use quality applicator tools. Do not sacrifice good results by using inexpensive tools. Apply only when surface and air temperatures are between 50°F and 90°F.</p>						
NOTE: Formulated without mercury or lead.								

Resin Type:	Acrylic / Vinyl Acrylic
Solids:	Volume Solids: 34
Weight Per Gallon:	10.45 lbs. per gallon
Viscosity:	100 – 104 (Krebs Units)
Specular Gloss:	3.5 – 6.0% @ 60° 10 – 12% @ 85°
Recommended Film Thickness:	Wet – 3.5 to 4.0 mils Dry – 1.20 to 1.35 mils
Spread Rate:	400 – 450 sq. ft. per gallon.
VOC – VOS Statement:	This product contains a maximum of 100 grams of VOC/VOS per liter of coating (.83 lbs. per gallon)
Cautions:	CAUTION! Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN.